



TB-100LP "Low Profile" Hydraulic Carrier Series



5" LOWER DECK HEIGHT OVER MOST CONVENTIONAL CARRIERS

Standard Features:

- § 19' steel or aluminum bodies
- § 8,000 lb hydraulic worm gear winch
- § 50' x 3/8" cable / Tensioner / Freewheel ext.
- § PTO / Pump & all hydraulics
- § Cat-trac hose protection system
- § Aluminum, bolt-on, blade siderails
- § Side tool compartment
- § Dual rear control stations w/ LED lighting
- § Custom high tapered light pylon
- § Full length body polymer wear pads
- § Independent wheelift apparatus complete w/ slider arms, L-arms, ratchets, and wheel restraint straps
- Mud flaps
- § Federal light package #108-LED
- § Hookup & safety chain package
- §

Low profile deck height for easier access to tie downs.



Lower approach angle for increased load clearance!

Ratings*

- § 10,000 lb. platform rating
- § 8,000 lb. SAE Rated worm gear winch
- § 4,000 lb. wheel lift rating

Optional Features:

- § Custom requests - Permanent open tube siderails / Removable siderails
- § Barlights / Strobe lights / Spot lights / Work lights / LED lighting
- § Planetary gear winch in lieu of standard
- § Engine mount clutch pump
- § Front pushplates / Karstarts
- § Stainless decor packages
- § Additional rear spring buildup
- § Custom modifications as desired

Chassis Recommendations:

- § 19,500 lb. GVW chassis
- § 120" CA dimension
- § Forward frame fuel tank - no rear tank
- §

** All ratings specified are based on structural factors only, not vehicle or chassis capabilities. Body rating is water load level rating with weight evenly distributed. Specifications are subject to change without notice.*

Able WeldBuilt Industries Inc.

1030 Grand Blvd., § Deer Park, N.Y. 11729

Phone: (631) 643 - 9700 Fax: (631) 491 - 4728

Web Address: www.weldbuilt.com

*Deck heights and load angles vary according to chassis specifications.

Additional customizing available upon request!